

Specifications of EN-500 x 2 Machine

EN-500 x 2 is a single station bi-axial rotational molding machine with one straight arm, which has capacity to mount a two molds of 500 liter or 300 liter.

EN-500 x 2 is most fuel efficient rotational molding machine with low man power requirement and hence the production cost is very low.

EN-500 x 2 includes the following equipments:-

1. Oven Chamber:

The oven chamber is constructed of stainless steel. To reduce heat losses an insulation of 75 mm is used. The oven is very compact and hence fuel efficient. The oven door has an inspection window. Top loading system is provided with ladder for producing multi-layer tanks. The oven is painted with Polyurethane paint for better appearance and long life.

2. Burner:

Italian "REILLO" make burner **RL 40 G20**, which is suitable for **Diesel** as a fuel. The burner is most fuel efficient with low noise and smoke free firing. A two stage 10 micron filter is used for higher efficiency and low maintenance. It has flame failure indication along with safety feature which meets International safety standards. LPG and Natural Gas Burner **FS 20** is optional at extra cost.

3. Re-Circulating Blower:

The impeller is made of stainless steel and is dynamical balanced. It is a high capacity, low R.P.M and low noise blower. The blower shaft is supported on both sides with maintenance free high quality bearing. 1.5 Hp LHP standard motor is used to run blower. Standard taper lock pulleys are used.

4. Straight Arm:

Heavy duty straight arm can take up a moulds of 500 liter x 2 or 300 ltr x 2. Moulds rotate in both X and Y directions with 6 R.P.M max. Variable speed A.C drive duty motors are provided. Heavy duty gear box is used for smooth operation. Chain drive is used for low maintenance. Mould mounting is very easy & fast.

5. Control Panel:

A user friendly control panel with adjustable mounting is provided with furnace. **Toshiba** or **Schneider** make drives are used for controlling speed of major and minor axis motor. For getting uniform thickness auto reversal facility is provided. Digital voltmeter for three phases, digital temperature controller, phase indicator lamp, and cycle timer are provided for easy operation & control. Hooter, flame failure lamp, safety interlocks are provided for safety purpose.

Operating Parameters.

- | | |
|--------------------------|--|
| 1. Production Per Cycle: | 500 ltr x 2 or 300 ltr x 2 . |
| 2. Total Cycle Time: | 60 min.(Heating: 25min,Cooling: 20min, Loading unloading:15min.) |
| 3. Production Per day: | 20,000 lit. Max (24 hrs). |
| 4. Production Capacity: | 40 tanks of 500 ltr or 40 tanks of 300 Ltr (24 Hrs). |
| 5. Electrical Load: | 3.5 Hp (415 volt 3 phase). |
| 6. Diesel Consumption: | 3.5 liter/cycle |
| OR | |
| Gas Consumption: | 2.9 kg/cycle |

7. Process Temperature: 180 degree.
8. Space for Machine: L 3.7mtr x W 2.4 mtr x H 4.5 Mtr
9. Machine suitable for: Double layer, Triple layer, Four layer and Foam /Insulated tank.
10. Manpower: 2 Semi skilled persons.

Technical Specifications:

Model No. : EN-500x 2

Spindles.....	1
Maximum Weight on Straight Arm.....	150 Kg
Spider Diameter.....	800 mm
Major Axis R.P.M. (x-axis).....	0-6
Minor Axis R.P.M. (y-axis).....	0-6

Furnace / Oven

Maximum Kcal / Hr.....	2,00,000
Usage Normal (Kcal/cycle).....	33,000
Maximum Temperature °C.....	250.0
Circulating Blower C.F.M.....	4500

Electrical

Supply Voltage.	415 V, 50 Hz, 3 Ph & Neutral
Oven Circulating Blower H.P (1 Nos.).....	1.5 HP
Major Axis Drive AC Motor H.P.....	1.0 HP
Minor Axis Drive AC Motor H.P.....	0.5 HP
Burner H.P.....	0.5 HP

Scope Of Our Supply :

Scope of supply includes machine and control panel as specified above.

Customer will have to provide for


- 1) Plain and level ground for installation of machine.
- 2) Electrical connection up to panel.
- 3) Erection and commissioning as per agreed terms.
- 4) Diesel storage tank/ gas pipe line up to the burner.

Note:

Vinodrai also manufacture touch screen PLC based control panel on buyer's demand. It's a semi-automatic panel with ALEN BRADLY make PLC.

❖ Specification is subjected to improvement and development.

Vinodrai Engineers Pvt Ltd



MODEL: EN-500X2

Specification EN 500 x 2